



P.C.B Layout

DIM.	Poles	A	B	C
2	4.25	1.25	7.55	
3	5.50	2.50	8.80	
4	6.75	3.75	10.05	
5	8.00	5.00	11.30	
6	9.25	6.25	12.55	
7	10.50	7.50	13.80	

DIM.	Poles	A	B	C
8	11.75	8.75	15.05	
9	13.00	10.00	16.30	
10	14.25	11.25	17.55	
11	15.50	12.50	18.80	
12	16.75	13.75	20.05	
13	18.00	15.00	21.30	

DIM.	Poles	A	B	C
14	19.25	16.25	22.55	
15	20.50	17.50	23.80	
16	21.75	18.75	25.05	
17	23.00	20.00	26.30	
18	24.25	21.25	27.55	

■ 技术参数 SPECIFICATIONS

- ◆ 适用线规：AWG#28~#32
- ◆ Applicable Wire: AWG#28~#32
- ◆ 额定电压：125V DC,AC(rms)
- ◆ Rated voltage: 125V DC,AC(rms)
- ◆ 额定电流：1A
- ◆ Rated Current: 1A
- ◆ 耐压值：500V AC/minute
- ◆ Withstand voltage: 500V AC/min.
- ◆ 工作温度：-25°C ~ +85°C
- ◆ Working Temp：-25°C ~ +85°C
- ◆ 绝缘电阻：≥ 1000 MΩ
- ◆ Insulation resistance: ≥ 1000 MΩ
- ◆ 接触电阻：≤ 20mΩ
- ◆ Contact resistance: ≤ 20mΩ

ITEM	PART NAME	TER.NO.	QTY.	MATERIAL	FINISHING	REMARK
③	Solder Tab	—	2	Phosphor bronze	Ag-PLATED	—
②	PIN	—	—	Phosphor bronze	Ag-PLATED	—
①	Base	—	1	PA46	—	—

APPROVALS	DATE	TITLE:
DRAWN	JIANKUN.LIU	2015.03.17
CHECKED		FPC
APPROVALS		1.25T-1P-1T

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

TOLERANCES ARE	30~12.5	10~30	5~10	~5	±0.30	±0.20	±0.15	±0.10	ANGLE	UNIT:	SCALE:	DRAWING NO.	PROJ:	SHEET
									±2°	mm	1:1			1 OF 1

