ROHS

http://www.smtswitch.com





SCHEMATIC



SPECIFICATIONS:

1. ELECTRICAL CHARACTERISTICS:
   - 1−1. RATING: 20V, 7A Min.
   - 1−2. CONTACT RESISTANCE:
     50 MILLIOHMS Max. FOR INITIAL,
     80 MILLIOHMS Max. AFTER 5000 CYCLES.
   - 1−3. INSULATION RESISTANCE: 100 MEGAOHMS Min.
     BY 500V DC AFTER 1 MINUTE.
   - 1−4. DIELECTRIC WITHSTANDING VOLTAGE: 500V
     RMS AFTER 1 MINUTE.
2. MECHANICAL CHARACTERISTICS:
   - 2−1. INSERTION FORCE : 0.3~3.0 KGF(2.94~29.4N)
   - 2−2. WITHDRAWAL FORCE : 0.3~3.0 KGF(2.94~29.4N)
3. LIFE TEST: 5,000 CYCLES MIN.



Cutaway View

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
②	Terminal	———	3	Copper	Ni Plating	———
①	Housing	———	1	PBT	Black	———

APPROVALS		DATE	HRO 韩京® ELECTRONICS CO.,LTD
DRAWN	JKUN.LU	2013/11/11	
CHECKED			TITLE: DC PLUG
APPROVALS			PART NO. DC−192G
TOLERANCES ARE	30~以下 ±0.30; 10~30 ±0.20; 5~10 ±0.15; ~ 5 ±0.10	ANGLE ±2°	UNIT: mm; SCALE: 1:1; PROJ: ; DRAWING NO. ———; SHEET 1 OF 1

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
———	A	———	NEW	———	———	———