


- Typical Specifications
1. Rating : 5A120V AC
 2. Insulation Resistance:1,000M min
 3. Dielectric Strength:1,500V RMS
 4. Operating Life : 30,000 cycles



Circuit Diagram

PART NO	vigor
1	300±100

PCB Layout(pattern side)

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
⑤	Terminal	—	6	Copper	Plating silver	—
④	Contact	—	1	FAg/C5210	—	—
③	Base	—	1	PA	Black	—
②	Cover	—	1	SPCC	Plating Sn	—
①	Keystoke	—	1	PA	RED	—

APPROVALS	DATE	ELECTRONICS CO.,LTD	
DRAWN	JIANKUN.LIU	2015.05.25	

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			
TOLERANCES ARE				30 ^{±0.1}	±0.30	ANGLE
				10 ^{±0.30}	±0.20	UNIT: mm
				5 ^{±0.10}	±0.15	SCALE: 1:1
				~ 5	±Z	DRAWING NO.
APPROVALS				PART NO. K3-2391C		
CHECKED				TITLE: Side SWITCHS		
DRAWN				PROJ:		
DATE				SHEET 1 OF 1		