



PIN NO.	PIN NAME
C 1	Supply Voltage Vcc
C 2	Reset (RST)
C 3	Clock (CLK)
C 4	N/A
C 5	Ground
C 6	Programming Voltage Vpp
C 7	I/O
C 8	N/A

SIM CARD(2:1)

- Specification:
- 1.Current rating:1.0 AMP
 - 2.Voltage rating: 12V DC
 - 3.Dielectric strength:500V AC RMS for 1 minute.
 - 4.Contact resistance:30mΩ
 - 5.Insulator resistance:500MΩ max.
 - 6.Mating un mating cycles:5000 cycles
 - 7.Packaging: 600pcs/Reel

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
③	Shell	—	1	SUS	Ni Plated	
②	Terminal	—	6	Phosphor Bronze	Sn Plated	
①	Housing	—	1	LCP	Black	

APPROVALS	DATE	TITLE:
DRAWN JKUNLU	2014/9/29	SIM
CHECKED		ELECTRONICS CO.,LTD
APPROVALS		

TOLERANCES ARE	ANGLE	UNIT:	SCALE:	DRAWING NO.	SHEET
30~12.5 ±	±0.30	mm	1:1		1 OF 1
10~30	±0.25				
5~10	±0.20				
~5	±0.15				