



Recommended PCB Layout

SPECIFICATIONS

- 1.RATING: DC30V 1.0A
- 2.MECHANICAL LIFE: 10,000 CYCLES.
- 3.PACKAGING: 1000PCS/REEL

| | | | | | | |
|------|-----------|---------|------|-----------------|-----------|--------|
| ③ | Shell | — | 1 | Phosphor Bronze | Sn Plated | |
| ② | Contact | — | 5 | Phosphor Bronze | Au Plated | |
| ① | Housing | — | 1 | LCP | Black | |
| ITEM | PART NAME | TER'NO. | QTY. | MATERIAL | FINISHING | REMARK |

| | | | | | | |
|-----------|---------|-----------|---------------------|--|--|--|
| APPROVALS | | DATE | ELECTRONICS CO.,LTD | | | |
| DRAWN | JKUN.LU | 2014/9/29 | | | | |
| CHECKED | | | | | | |
| APPROVALS | | | | | | |

| | | | | | | | | | | | | |
|---------|------|-------|--------------|---------|--------|--------|--------------------------------------|-------|-------|--------|--------------|--------|
| ECN NO. | REV. | DATE. | DESCRIPTION. | CHANGE. | CHECK. | APPRO. | TOLERANCES ARE | ANGLE | UNIT: | SCALE: | PROJ: | SHEET |
| | A | | NEW | | | | 30 ^{+0.12} _{-0.10} | ±2° | mm | 1:1 | U-F-M5DS-W-1 | 1 OF 1 |