



PCB LAYOUT

- SPECIFICATIONS
- 1、Current Rating: 3A AC, DC
 - 2、Voltage Rating: 250V AC, DC
 - 3、Temperature Range: -25°C~+85°C
 - 4、Contact Resistance: 10mΩ Max
 - 5、Insulation Resistance: 1000MΩ Min
 - 6、Withstanding Voltage: 1000V AC/minute
 - 7、Material: Wafer LCP, UL94V-0
PIN Brass Tin-plated
Solder tabs Brass Tin-plated

| 编 号 | 尺寸 (mm) | | | |
|-------------|---------|-------|-------|-------|
| | A | B | C | D |
| A2501WF-02A | 2.50 | 7.50 | 10.00 | 8.20 |
| A2501WF-03A | 5.00 | 10.00 | 12.50 | 10.70 |
| A2501WF-04A | 7.50 | 12.50 | 15.00 | 13.20 |
| A2501WF-05A | 10.00 | 15.00 | 17.50 | 15.70 |
| A2501WF-06A | 12.50 | 17.50 | 20.00 | 18.20 |
| A2501WF-07A | 15.00 | 20.00 | 22.50 | 20.70 |
| A2501WF-08A | 17.50 | 22.50 | 25.00 | 23.20 |
| A2501WF-09A | 20.00 | 25.00 | 27.50 | 25.70 |
| A2501WF-10A | 22.50 | 27.50 | 30.00 | 28.20 |
| A2501WF-11A | 25.00 | 30.00 | 32.50 | 30.70 |
| A2501WF-12A | 27.50 | 32.50 | 35.00 | 33.20 |
| A2501WF-15A | 35.00 | 40.00 | 42.50 | 40.70 |

变更内容 DESCRIPTION 日期 DATE

GENERAL TOLERANCE 制 图 料号 PART NO. A2501WF-NA
X.±0.25 X.±2*
.X±0.20 X.±1*
.XX±0.15 .XX±0.5*
.XXX±0.10 .XXX±0.5*
单位 UNITS MM 比例 SCALE 1:1

审 核 品 名 版本 REV. A
核 准 客户料号 TITLE 页次 1/1
CIRCU. NO. SHEET

